

طلب عروض فنية وسعريية لمغاسل طبقاً للمواصفات المرفقة موضح بها الآتي:

1- الأسعار على أساس التوريد : DAP (INCOTERMS 2010) .

2- المواصفات الفنية كاملة مرفق بها كتالوج باللغة الإنجليزية على النحو التالي :

أ - عدد (3) نسخة من العرض الفني بدون أسعار ومدون بها كافة الشروط التعاقدية .

ب - عدد (1) نسخة من العروض مدون بها الأسعار ومدون بها كافة الشروط التعاقدية .

ج - DECLARATION OF CONFIDENTIALITY طبقاً للنموذج .

د - IDENTIFICATION FORM طبقاً للنموذج .

هـ - SIMPLIFIED BALANCE SHEET طبقاً للنموذج .

3- مدة صلاحية العروض حتى : أطول فترة ممكنة .

4- شروط الدفع : إعتقاد مستندى .

5- مدة التوريد : أقل مدة ممكنة .

6- التفيتيش والتدريب : سيتم مناقشته أثناء الممارسة والتعاقد .

7- آخر موعد لتلقى العروض : 17 مارس 2020.

كشف بالأصناف المطلوب التعاقد عليها

RFQ	EQUIPMENT	QTY
1	AUTOMATIC WASHER EXTRACTOR DRUM VOLUME: 550 LIT CAPACITY :61 KG/LOAD G-VALUE: 130 POWER: ELECTRIC	
2	AUTOMATIC WASHER EXTRACTOR DRUM VOLUME: 226 LIT CAPACITY :25 KG/LOAD G-VALUE:141 POWER: ELECTRIC	
3	DRYER DRUM VOLUME: 1080 LIT CAPACITY: 60 KG/LOAD S/S DRUM GAS HEATED	
4	DRYER DRUM VOLUME: 1080 LIT CAPACITY: 60 KG/LOAD S/S DRUM POWER: ELECTRIC	
5	DRYER DRUM VOLUME: 460 LIT CAPACITY: 25 KG/LOAD S/S DRUM GAS HEATED	
6	DRYER DRUM VOLUME: 460 LIT CAPACITY: 25 KG/LOAD S/S DRUM POWER: ELECTRIC	
7	DRYER DRUM VOLUME: 660 LIT CAPACITY: 37 KG/LOAD S/S DRUM POWER: ELECTRIC	
8	FLAT WORK IRONER 1 ROLL 51 CM DIAM. X 253 CM LENGTH PRODUCTION: 80 KG/HR. (%50 HUMIDITY)	

كشف بالأصناف المطلوب التعاقد عليها

RFQ	EQUIPMENT	QTY
	POWER: ELECTRIC	
9	FLAT WORK IRONER 1 ROLL DIAM. 32CM X 212CM LENGTH PRODUCTION: 40 KG/HR. (%50 HUMIDITY) POWER: ELECTRIC	
10	FLAT WORK IRONER 1 ROLL 51 CM DIAM. X 316 CM LENGTH PRODUCTION: 120 KG/HR. (%50 HUMIDITY) GAS HEATED	
11	ELECTRICALLY HEATED TABLES WITH BOILER BUILT-IN VACUUM UNIT ELECTRIC & AUTOMATIC STEAM BOILER, C/W IRON	
12	DRY CLEAN – PRESS PNEUMATTICALLY DRIVEN PRESS – DRY CLEAN BUILT IN VACUUM WITH BOILER TWO PUSH BOTTONS	

CLIN	Nomenclature	QTY
<u>كشف بالإصناف المطلوب التعاقد عليها</u>		
lundry		
1	<p>Washer Extractor Electric Heated Rigid mounted, normal spin Xcontrol - easy to use microprocessor Multilingual (25 languages) & USB port) Large drain valve (Ø 76 mm) Easy access to all vital parts from the front Stainless steel top panel & Anthracite grey front and side panels (15 cycles , Fully programmable , Graphic display , Patented Soap Hopper Large door opening for easy loading & unloading maximum capacity 1:9 : 27 kg capacity 1:10 : 24 kg G-Factor : 100 Drum volume : 240 l Drum diameter : 750 mm Standard Frequency controlled motor Standard wash speed : 42 rpm Max. spin speed : 490 rpm Dimensions (H×W×D) : 1410×890×1060 mm</p>	8
2	<p>WASHER EXTRACTOR Capacity: 52 kg Rigid mounted Heating: ELECTRIC Power supply: 3x380-415Vx50Hz + N Standard XControl (easy to use) Standard stainless steel top Standard anthracite grey painted front and side panels Standard Easy Soap system Standard provided for steam connection Standard film crate packing</p>	2

CLIN	Nomenclature	QTY
3	<p>INDUSTRIAL TUMBLE DRYER Electric heating Cap. : 25 kg Cylinder volume: 528 lt Drum dim. : Φ 939 mm Dual digital timer (OPL) Stainless steel drum Standard Stainless steel look panels (side and front) Large door opening for easy loading and unloading Airflow : 330 l/s Electrical heating : 30 kW Electrical connection :380/50-60/3PH</p>	8
4	<p>INDUSTRIAL TUMBLE DRYER Electric heating Cap. : 34 kg Cylinder volume: 634 lt Dual digital timer (OPL) Stainless steel drum Standard Stainless steel look panels (side and front) Large door opening for easy loading and unloading Electrical heating : 36 kW Electrical connection : 3\times380-50/60Hz Dimensions: (HxWxD) (1960\times980\times1350 mm) Net Weight (kg) 279</p>	2
5	<p>FLATWORK IRONER Electric heating Number of rolls: 1 Diameter roller : 29 cm Useful length roller: 200 cm Capacity per hour : 52 -79kg Return of the linen : Front Side Roller speed : 2-4 Safety fi nger protection and emergency button for more safety Foot pedal for easy start and stop operation Electric: 17 kw / 400/50/3</p>	8